

Need more information? [Click Here](#) to go to the UL iQ™ for Plastics database

Component - Plastics

**E350602**

## ELIX POLYMERS SL

POLIGONO INDUSTRIAL, APARTADO DE CORREOS 176, CTRA DE VILA-SECA A LA PINEDA,  
TARRAGONA 43080 ES

## P2HE

**Acrylonitrile Butadiene Styrene (ABS), "ELIX ABS", furnished as pellets**

| Color | Min Thk<br>(mm) | Flame<br>Class | HWI |     | RTI  |     | RTI<br>Str |
|-------|-----------------|----------------|-----|-----|------|-----|------------|
|       |                 |                | HWI | HAI | Elec | Imp |            |
| ALL   | 1.5             | HB             | 4   | 0   | 60   | 60  | 60         |
|       | 3.0             | HB             | 4   | 0   | 60   | 60  | 60         |

Comparative Tracking Index (CTI): **0**

Inclined Plane Tracking (IPT): -

Dielectric Strength (kV/mm): **22**

Volume Resistivity (10<sup>x</sup> ohm-cm) : **15**

High-Voltage Arc Tracking Rate  
(HVTR): **2**

High Volt, Low Current Arc Resis (D495): **6**

Dimensional Stability (%): **0**

ANSI/UL 94 small-scale test data does not pertain to building materials, furnishings and related contents. ANSI/UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in the components and parts of end-product devices and appliances, where the acceptability of the combination is determined by UL.

Report Date: 1973-07-23

Last Revised: 2011-10-20

© 2011 Underwriters Laboratories Inc.



## IEC and ISO Test Methods

| Test Name                      | Test Method     | Units             | Thickness   |  | Value      |
|--------------------------------|-----------------|-------------------|-------------|--|------------|
|                                |                 |                   | Tested (mm) |  |            |
| Flammability                   | IEC 60695-11-10 | Class (color)     | 1.5         |  | HB75 (ALL) |
|                                |                 |                   | 3.0         |  | HB40 (ALL) |
| Glow-Wire Flammability (GWI)   | IEC 60695-2-12  | C                 | -           |  | -          |
| Glow-Wire Ignition (GWIT)      | IEC 60695-2-13  | C                 | -           |  | -          |
| IEC Comparative Tracking Index | IEC 60112       | Volts (Max)       | -           |  | -          |
| IEC Ball Pressure              | IEC 60695-10-2  | C                 | -           |  | -          |
| ISO Heat Deflection (1.80 MPa) | ISO 75-2        | C                 | -           |  | -          |
| ISO Tensile Strength           | ISO 527-2       | MPa               | -           |  | -          |
| ISO Flexural Strength          | ISO 178         | MPa               | -           |  | -          |
| ISO Tensile Impact             | ISO 8256        | kJ/m <sup>2</sup> | -           |  | -          |
| ISO Izod Impact                | ISO 180         | kJ/m <sup>2</sup> | -           |  | -          |
| ISO Charpy Impact              | ISO 179-2       | kJ/m <sup>2</sup> | -           |  | -          |

© 2011 Underwriters Laboratories Inc.

The materials covered in this database are incomplete in certain constructional features or restricted in performance capabilities and are intended for use as components of complete equipment submitted for investigation rather than for direct separate installation in the field. THE FINAL ACCEPTANCE OF THE COMPONENT IS DEPENDENT UPON ITS INSTALLATION AND USE IN COMPLETE PRODUCTS SUBMITTED TO UNDERWRITERS LABORATORIES.

Notice of Disclaimer