

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

 Revision date:
 24/4/2025

 Version:
 26.1

 Replaces version:
 26.0

 Language:
 en-EU

 Date of print:
 24/4/2025

ELIX ABS Pellets

Material number ELIX005 Page: 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: ELIX ABS Pellets

1.2 Relevant identified uses of the substance or mixture and uses advised against

General use: For the production of moulded plastic articles or as intermediate for the production of plastic

Reserved for industrial and professional use.

1.3 Details of the supplier of the safety data sheet

Company name: ELIX Polymers, S.L. Street/POB-No.: Polígono Industrial

Ctra. de Vilaseca - La Pineda

Postal Code, city: 43006 Tarragona, Spain

Spain

www.elix-polymers.com
E-mail: info@elix-polymers.com
Telephone: +34-977-835400

Department responsible for information:

Telephone: +34-977-835476, E-mail info@elix-polymers.com

Additional information: This safety data sheet pertains to all the products listed in chapter 16.

1.4 Emergency telephone number

Telephone: +1 760 476 3961

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to EC regulation 1272/2008 (CLP)

This mixture is classified as not hazardous.

2.2 Label elements

Labelling (CLP)

Hazard statements: not applicable
Precautionary statements: not applicable

2.3 Other hazards

Under the recommended processing conditions small amounts of emitted substance (e.g. residual monomers, residual solvents, decomposition products) may be discharged. In succession of overheating during the melting process potentially substances are released, which are considered as harmful and carcinogen. The maximum workplace exposure limits are, where necessary, listed in section 8.

The melted product can cause severe burns.

Endocrine disrupting properties, Results of PBT and vPvB assessment:

No data available



according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

 Revision date:
 24/4/2025

 Version:
 26.1

 Replaces version:
 26.0

 Language:
 en-EU

 Date of print:
 24/4/2025

ELIX ABS Pellets

Material number ELIX005 Page: 2 of 10

SECTION 3: Composition/information on ingredients

3.1 Substances: not applicable

3.2 Mixtures

Chemical characterisation: Acrylonitrile-butadiene-styrene copolymer

Additional information: The product does not contain dangerous substances above limits that need to be

mentioned in this section according to applicable EU-legislation.

SECTION 4: First aid measures

4.1 Description of first aid measures

In case of inhalation of decomposition products, affected person should be moved into

fresh air and kept still. In case of breathing difficulties administer oxygen. If breathing has

stopped, give artificial respiration immediately. Seek medical attention.

Following skin contact: After contact with molten product, cool skin area rapidly with cold water. Do not use force

or solvents to remove product incrustations from affected skin areas. Cover wounds with sterile dressing. Take off contaminated clothing and wash it before reuse. Seek medical

attention.

After eye contact: Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids

apart. Remove contact lenses, if present and easy to do. Continue rinsing. In case of

troubles or persistent symptoms, consult an opthalmologist.

After swallowing: Rinse mouth with water. Drink one or two glasses of water.

Never give an unconscious person anything through the mouth, seek medical attention

4.2 Most important symptoms and effects, both acute and delayed

Dust: Skin irritation, eye irritations and redness

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media:

water spray jet, foam, dry extinguishing powder, carbon dioxide.

5.2 Special hazards arising from the substance or mixture

In case of fire may be liberated: Nitrogen oxides (NOx), carbon monoxide and carbon dioxide.

5.3 Advice for firefighters

Special protective equipment for firefighters:

Wear self-contained breathing apparatus. Suitable protective clothing.

Additional information: Seal off endangered area. Remove persons to safety.

Do not allow water used to extinguish fire to enter drains, ground or waterways.



according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

 Revision date:
 24/4/2025

 Version:
 26.1

 Replaces version:
 26.0

 Language:
 en-EU

 Date of print:
 24/4/2025

ELIX ABS Pellets

Material number ELIX005 Page: 3 of 10

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep the molten mass away from the eyes and the skin.

Where there is a risk of exothermal decomposition as a result of overheating (rise in temperature, formation of fumes or smoke), cool the melt in a water bath. Do not breathe vapours. Wear appropriate protective equipment. Take off contaminated clothing and wash it before reuse. Provide adequate ventilation. Provide a conveniently located respiratory protective device.

6.2 Environmental precautions

Avoid release to the environment.

6.3 Methods and material for containment and cleaning up

Take up mechanically.

Additional information: Granulate: Special danger of slipping by leaking/spilling product.

6.4 Reference to other sections

Refer additionally to section 8 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advices on safe handling: In case of melting: To avoid thermal decomposition, do not overheat.

Make sure there is sufficient air exchange and / or that working rooms are air suctioned.

Avoid exceeding WEL threshold levels. Do not breathe vapours.

After work, wash hands and face. Wear appropriate protective equipment. Take off

contaminated clothing and wash it before reuse.

For mechanical processing:

Do not breathe dust. Vent dust from the work area.

Avoid dust formation during regranulation. Safety shower and eye wash station should be

easily accessible to the work area.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storerooms and containers:

Keep container dry. Store only in original container.

Hints on joint storage: Keep away from food, drink and animal feedingstuffs.

7.3 Specific end use(s)

No information available.



according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

 Revision date:
 24/4/2025

 Version:
 26.1

 Replaces version:
 26.0

 Language:
 en-EU

 Date of print:
 24/4/2025

ELIX ABS Pellets

Material number ELIX005 Page: 4 of 10

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values:

CAS No.	Designation	Туре	Limit value
100-41-4	Ethylbenzene	Europe: IOELV: STEL	884 mg/m³; 200 ppm (may be absorbed through the skin)
		Europe: IOELV: TWA	442 mg/m³; 100 ppm (may be absorbed through the skin)
106-99-0	1,3-Butadiene	Europe: BOELV: TWA	2.2 mg/m³; 1 ppm

Additional information:

Information about acrylonitrile and butadiene: carcinogenic effect.

Additional protective measures:

- Measurements for the early detection of increased exposure as a result of an unforeseen incident:
- The danger areas must be delimited and identified using relevant warning and safety signs. Smoking is forbidden.
- The exhaust air must only be let back to the working area after sufficient cleaning using approved equipment.

8.2 Exposure controls

In case of melting:

Provide for good ventilation or exhaust system or work with completely self-contained equipment.

Personal protection equipment

Occupational exposure controls

Respiratory protection: In case of dust formation: Particulates filter P1 according to EN 143.

Respiratory protection must be worn whenever the WEL levels have been exceeded. Use filter type A (= against vapours of organic substances) according to EN 14387.

Hand protection: Chemically resistant gloves according to EN 374 or

In case of melting: Protective gloves against thermic risks according to EN 407.

Glove material: Leather.

Observe glove manufacturer's instructions concerning penetrability and breakthrough time.

Eye protection: Tightly sealed goggles according to EN ISO 16321-1.

Body protection: Wear suitable protective clothing.

In case of dust formation: Overall

General protection and hygiene measures:

Take off contaminated clothing and wash it before reuse.

Wash contaminated clothing prior to re-use. When using do not eat, drink or smoke. Wash hands before breaks and after work.

Safety shower and eye wash station should be easily accessible to the work area.



according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

Revision date: 24/4/2025 Version: 26.1 Replaces version: 26.0 Language: en-EU Date of print: 24/4/2025

ELIX ABS Pellets

Material number ELIX005 Page: 5 of 10

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state at 20 °C and 101.3 kPa solid

Form: granulate

Colour: varying

Odour: characteristic

Melting point/freezing point: Softening temperature: 90 - 105 °C

Boiling point: Decomposition temperature: > 300 °C

Flammability: HB (SADT)
Lower and upper explosion limit: Not applicable
Flash point: Not applicable
Auto-ignition temperature: Not applicable
Decomposition temperature: > 300 °C

pH: Not applicable
Kinematic viscosity: Not applicable
Water solubility: Insoluble

Partition coefficient n-octanol/water (log value):

No data available

Vapour pressure:

Density:

No data available
at 20 °C: 1.05 g/cm³

Relative vapour density:

Not applicable

Particle characteristics: Particle size: < 5mm

9.2 Other information

Explosive properties:

No data available

Oxidizing characteristics:

No data available

Auto-ignition temperature: No data available
Bulk density: 500 - 700 kg/m³

Additional information: Burning rate: 50 - 60 mm/min.

Maximum heat flow (TAM): < 0.05 mW/g

SECTION 10: Stability and reactivity

10.1 Reactivity

exothermic reactions

10.2 Chemical stability

Stable under recommended storage conditions.



according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

 Revision date:
 24/4/2025

 Version:
 26.1

 Replaces version:
 26.0

 Language:
 en-EU

 Date of print:
 24/4/2025

ELIX ABS Pellets

Material number ELIX005 Page: 6 of 10

10.3 Possibility of hazardous reactions

No hazardous reactions known.

10.4 Conditions to avoid

Protect against heat /sun rays. Decomposition!

10.5 Incompatible materials

No data available

10.6 Hazardous decomposition products

No hazardous decomposition products when regulations for storage and handling are

observed.

Thermal decomposition: > 300 °C

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological effects: Acute toxicity (oral): Lack of data.

Acute toxicity (dermal): Lack of data. Acute toxicity (inhalative): Lack of data. Skin corrosion/irritation: Lack of data.

Serious eye damage/irritation: Lack of data.

Sensitisation to the respiratory tract: Based on available data, the classification criteria

are not met.

Skin sensitisation: Based on available data, the classification criteria are not met.

Germ cell mutagenicity/Genotoxicity: Based on available data, the classification criteria

are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

Effects on or via lactation: Lack of data.

Specific target organ toxicity (single exposure): Lack of data.

Specific target organ toxicity (repeated exposure): Based on available data, the

classification criteria are not met.

Aspiration hazard: Lack of data.

11.2 Information on other hazards

Endocrine disrupting properties:

No data available

Other information: There are no known health risks.

Under the recommended processing conditions small amounts of emitted substance (e.g. residual monomers, residual solvents, decomposition products) may be discharged. In succession of overheating during the melting process potentially substances are

released, which are considered as harmful and carcinogen.

The melted product can cause severe burns.



according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

Revision date: 24/4/2025 Version: 26.1 Replaces version: 26.0 Language: en-EU Date of print: 24/4/2025

ELIX ABS Pellets

Material number ELIX005 Page: 7 of 10

SECTION 12: Ecological information

12.1 Toxicity

Further details: No data available

12.2 Persistence and degradability

Further details: Product is not readily biodegradable.

Due to the consistency along with the low water solubility of the product a bioavailability

is unlikely.

12.3 Bioaccumulative potential

Partition coefficient: n-octanol/water:

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

General information: Discharge into the environment must be avoided.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste key number: 07 02 13 = Waste plastic

Recommendation: Recycling or special waste incineration.

After appropriate treatment the product can be remelted and reprocessed into new moulded articles. Mechanical recycling is only possible if the material has been

selectively retrieved and carefully segregated according to type.

Package

Recommendation: Non-contaminated packages may be recycled. If recycling is not practicable, dispose of

in compliance with local regulations.

Section 14. Transport information

14.1 UN number or ID number

ADR/RID, ADN, IMDG, IATA-DGR:

not applicable



according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

Revision date: 24/4/2025 Version: 26.1 Replaces version: 26.0 Language: en-EU Date of print: 24/4/2025

ELIX ABS Pellets

Material number ELIX005 Page: 8 of 10

14.2 UN proper shipping name

ADR/RID, ADN, IMDG, IATA-DGR:

Not restricted

14.3 Transport hazard class(es)

ADR/RID, ADN, IMDG, IATA-DGR:

not applicable

14.4 Packing group

ADR/RID, ADN, IMDG, IATA-DGR:

not applicable

14.5 Environmental hazards

Dangerous for the environment:

Substance/mixture is not environmentally hazardous according to the criteria of the UN model regulations.

Marine pollutant - IMDG: no

14.6 Special precautions for user

No dangerous good in sense of these transport regulations.

14.7 Maritime transport in bulk according to IMO instruments

No data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations - EC member states

Further regulations, limitations and legal requirements:

No data available

15.2 Chemical Safety Assessment

For this mixture a chemical safety assessment is not required.



according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

Revision date: 24/4/2025 Version: Replaces version: 26.0 Language: en-EU Date of print: 24/4/2025

ELIX ABS Pellets

Material number ELIX005 Page: 9 of 10

SECTION 16: Other information

This safety data sheet pertains to the following

products:

ELIX ABS 118HF-CC

ELIX 118HF

ELIX 118HF LNS020

ELIX ABS 3095 PG

ELIX ABS-3D GP

ELIX ABS-3D FC

ELIX ABS-3D HI

ELIX ABS-3D LA

ELIX ABS-3D HF

ELIX ABS C108

ELIX ABS C108-CC

ELIX ABS E310 **FLIX ABS E401**

ELIX ABS H604

ELIX ABS H604-CC

ELIX ABS H605

ELIX ABS H605-CC

ELIX ABS M201AS

ELIX ABS M201-CC

ELIX ABS M203

ELIX ABS M203-CC

ELIX ABS M203FC

ELIX ABS M205FC

ELIX ABS M210TF

ELIX ABS M220

ELIX ABS M220-CC

ELIX ABS M305

ELIX ABS M307

ELIX ABS M545TF

ELIX ABS P2H-AT ELIX ABS P2H-CC

ELIX ABS P2HE

ELIX ABS P2L-AT

ELIX ABS P2M-CC

ELIX ABS P2M-V

Reason of change: Changes in section 9: Physical and chemical properties

Date of first version: 30/12/2009

Department issuing data sheet:

see section 1: Department responsible for information

Abbreviations and acronyms

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

AS/NZS: Australian Standards/New Zealand Standards

CAS: Chemical Abstracts Service

CFR: Code of Federal Regulations

CLP: Classification, Labelling and Packaging

DMEL: Derived minimal effect level

DNEL: Derived no-effect level

EC: European Community

EmS: Emergency Response Procedures for Ships Carrying Dangerous Goods

printed by ELIX Polymers with Qualisys SUMDAT

ELIX ABS P2M

ELIX P2M-AT

ELIX ABS P2MC

ELIX ABS P3H-CC

ELIX ABS P3H-AT

ELIX ABS P3H-TF

ELIX ABS P3M-AT ELIX ABS P4LG

ELIX ABS E-LOOP H604 CR

ELIX ABS E-LOOP M203FC CR

ELIX ABS E-LOOP M203 MR

ELIX ABS E-LOOP M205FC CR

ELIX ABS E-LOOP M220 CR

ELIX ABS E-LOOP M220-CC CR

ELIX ABS E-LOOP P2H-AT CR

ELIX ABS E-LOOP P2H-CC CR

ELIX ABS E-LOOP P2H-AT MR

ELIX ABS E-LOOP P2MC CR

ELIX ABS E-LOOP P3H-AT CR

ELIX ABS M80390-CC

ELIX ABS M81835-CC

ELIX ABS M70400-CC

ELIX ABS M63312-CC

ELIX ABS M80830-CC

ELIX ABS M81232-CC

ELIX ABS K70085

ELIX ABS K80390



according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

Revision date: 24/4/2025 Version: 26.1 Replaces version: 26.0 Language: en-EU Date of print: 24/4/2025

ELIX ABS Pellets

Material number ELIX005 Page: 10 of 10

EN: European Standard

EQ: Excepted quantities

EU: European Union

IATA: International Air Transport Association

IATA-DGR: International Air Transport Association – Dangerous Goods Regulations

IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk

IMDG Code: International Maritime Dangerous Goods Code

IMO: International Maritime Organization

MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships

OEL: Occupational Exposure Limit Value

OSHA: Occupational Safety and Health Administration

PBT: Persistent, bioaccumulative and toxic PNEC: Predicted no-effect concentration

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals

RID: Regulations Concerning the International Carriage of Dangerous Goods by Rail

TLV: Threshold Limit Value

TRGS: Technical Rules for Hazardous Substances vPvB: Very persistent and very bioaccumulative

WEL: Workplace Exposure Limit

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.